

# Do It Right The First Time!

**SPICER®**  
brand components

When selling, or installing a new clutch, make sure that you recommend replacing all worn clutch release components with genuine Spicer® brand products. Consider the time and money associated with replacing a clutch and it only makes sense (\$) to complete the job by replacing all worn components.

TTC offers a complete line of high-quality yokes, cross shafts and brackets (all Spicer® brand) to complete any clutch replacement. Don't gamble with non-genuine components, specify Spicer® and "Do It Right The First Time."


If you don't see the components that you need, contact your TTC Spicer® brand distributor, or call TTC at (800) 401-9866.



**TTC**


1 800-401-9866  
[www.ttcautomotive.com](http://www.ttcautomotive.com)

# Clutch Release Components



## CR-7 Clutch Release Yokes\*


Type	Item #	Forging #	Width (J)	Bolt CL (K)	Inside Ear (M)	Note
Pull	<b>105C-137</b>	F105C138	8.000	6.500	4.895	
Pull	<b>105C-143</b>	F105C141	8.000	6.500	4.895	Extended Pivot Point (1.45 from C/L)
Pull	<b>105C-64</b>	F105C64	8.000	6.500	4.895	Clutch Release Pads - 30 Degree Offset
Push	<b>105C-117</b>	F105C118	8.375	7.000	4.885	Machined washer surface on yoke front
Push	<b>105C-124</b>	F105C125	3.750	2.125	2.885	
Push	<b>105C-130</b>	F105C94	3.750	2.125	2.885	
Push	<b>105C-132</b>	F105C118	8.375	7.000	4.885	Machined washer surface on yoke rear (for clearance)
Push	<b>85-509-3</b>	F105C118	8.375	7.000	4.885	Same as 105C-117, except contains spring holes in lug



**Pedal Adjusting Arm  
Right Side -310473X**

## CR-1 Short Release Shaft

Type	Length	Item #
RS-1	4.812	<b>106C-1278</b>
RS-1	5.750	<b>106C-1185</b>
RS-1	5.750	<b>62-510-22</b>
RS-1	6.000	<b>80-510-3</b>
RS-1	6.125	<b>106C-1142</b>
RS-1	6.500	<b>106C-1498</b>
RS-5	10.438	<b>106C-636</b>
RS-5	11.375	<b>106C-1515</b>
RS-5	14.000	<b>106C-438</b>



**Pedal Adjusting Arm  
Left Side-310233X**

## CR-6 Pedal Adjusting Arm Kit

Item #	Note
<b>310233X</b>	Left Side Mtg
<b>310473X</b>	Right Side Mtg
<b>310873X</b>	Lever Type 7.25 LH or RH


## Splined Thru Shaft (used with Push Type Clutch)

Length	Item #
19.125	<b>106C-1566</b>
19.313	<b>97-510-2</b>
19.500	<b>106C-1578</b>

## CR-2 Long Release Shaft

Type	Length	Item #	Type
Keyed	6.870	<b>106C-1589</b>	RS-10
Keyed	7.125	<b>46-510-9</b>	RS-10
Keyed	8.312	<b>106C-1529</b>	RS-3
Keyed	9.020	<b>97-510-7</b>	RS-10
Keyed	9.690	<b>97-510-5</b>	RS-10
Keyed	11.380	<b>97-510-6</b>	RS-10
Splined	7.625	<b>106C-1315</b>	RS-8
Splined	7.969	<b>106C-1083</b>	RS-8
Splined	8.250	<b>46-510-11</b>	RS-8
Splined	8.469	<b>106C-1094</b>	RS-8
Splined	8.719	<b>106C-960</b>	RS-8
Splined	8.968	<b>106C-1046</b>	RS-8
Splined	9.125	<b>106C-1169</b>	RS-8
Splined	9.220	<b>67-510-5</b>	RS-9
Splined	9.469	<b>106C-1047</b>	RS-8
Splined	9.469	<b>330610-5</b>	RS-9
Splined	9.500	<b>330610-10</b>	RS-9
Splined	9.750	<b>106C-953</b>	RS-8
Splined	10.000	<b>106C-939</b>	RS-8
Splined	10.312	<b>106C-1367</b>	RS-8
Splined	10.469	<b>106C-617</b>	RS-8
Splined	10.750	<b>330610-11</b>	RS-9
Splined	11.469	<b>106C-839</b>	RS-8
Splined	11.968	<b>106C-959</b>	RS-8

## Clutch Release Shafts



## To Order Clutch Release Shafts

1. Select Type from illustrations (left)
2. Determine lengths "A", "D" & "J"

In the tables above, only the more widely used Clutch Release Shafts are listed.

In the illustrations (left): Dimension "C" with a 0.250" Key Slot for 1-30 Round Key.

Dimension "B" with a 0.218" Notch for 330231 Screw.

\* CLUTCH RELEASE YOKE ATTACHING PARTS — use one KEY 10-30, two SCREWS 330231, and two LOCK WASHERS 500356-12.

**Are the parts you need not listed?  
Call 1-800-401-9866.**



A Kuo Automotriz Group Company

14700 Helm Court  
Plymouth, MI 48170  
Phone: (734) 456-3700  
FAX: (734) 456-3739  
www.ttcautomotive.com

Bulletin No. SPMM0150807